

VoIP en Mobiel

Vladdissel 9
1648 HJ De Goorn
info@voipenmobiel.nl
088-5017600

OS6870-48: Fixed chassis with 48x10/100/1000 RJ-45 2x100G QSFP28 VFL ports and 4x25G SFP28 ports

Artikelnummer: OS6870-48-EU



€16.519,00

Incl. 21% BTW

Description

The OmniSwitch 6870 combines versatile fabric support, strong security, and AI intelligence to create a flexible, secure, and low-maintenance platform tailored to meet a wide range of customer needs. This platform offers enhanced security, operational simplicity, and adaptable performance for the demands of modern network environments.

Specifications

- OmniFabric: SPB, VxLAN-EVPN2 and MPLS2
- Secure boot2
- Streaming network telemetry2 and DPI2
- 1588v2 End-to-End Transparent Clock
- Field replaceable redundant PSU both primary and backup
- Mix and match any supported PoE PSU redundancy to meet the PoE budget requirement while providing continues system operation
- The lowest power consumption level in similar class in term of wattage per switching capacity.
- Virtual chassis up to 8 with any model mix
- VFL stacking port can be used for uplink port in non-VC operation
- 1RU compact size with EMP (out-of-band management), console and USB ports
- Manage through Alcatel-Lucent OmniVista Cirrus Network Management System help visualize full wired wireless network to increase IT efficiency and business agility

[PDF DATASHEET](#)